

BudgetLink® (3 1/2" x 5" mesh - near total or semi privacy)
Patent Pending



BudgetLink® is an affordable chain link fence with single-wall privacy slats “pre-woven” into the chain link. It is the lowest priced fence in our pre-inserted family and it meets the needs of price conscious buyers in today’s tight economic environment. **BudgetLink®** is a rich looking chain link fence that greatly resembles premium fencing at a lower price. It provides the privacy and security you need around your property.

BudgetLink® Benefits:

- Virtual privacy or semi-privacy available
- Cost-efficient solution for most settings
- Less installation time saves on labor and costs
- Low maintenance
- Effective wind screen
- An exceptional sound barrier
- Virtually theft resistant
- Virtually unclimbable
- Available in seven attractive colors
- Available in two different privacy configurations for residential, industrial and commercial applications

HDPE Slats

Slats are single-wall, made from tough HDPE and “pre-woven” into the mesh for easy installation. There are seven attractive color options to choose from.

Galvanized Chain Link Fencing

We fabricate our chain link mesh using only the highest grade 9, 10 or 11 gauge galvanized wire. Our state-of-the-art manufacturing process ensures a consistent weave and product quality.

Vinyl Coated Chain Link Fencing

We also offer a fused and bonded vinyl coated chain link mesh that is color coordinated to seven of our standard slat colors. And, we guarantee it for years of trouble-free use.

ASTM Designations

Meets ASTM Designations (*see chart on the next page*)



Technical Data

BudgetLink® Specifications	
Wind load and privacy factor - Privacy (approx)	98%
Semi-Privacy (approx) (Based on wire/mesh used-stretch tension)	75%
3 1/2" x 5" Mesh	✓
Manufactured up to 8' high	✓
Available in 9 gauge galvanized before weaving (GBW) per ASTM A392 and A817, Type II, class IV wire (1.20 oz.)	✓
Available in 10 gauge galvanized before weaving (GBW) per ASTM A392 and A817, Type II, class IV wire (1.20 oz.)	✓
Available in 11 gauge galvanized before weaving (GBW), per ASTM A392 AND A817, Type II, class IV wire (1.20 oz.)	✓
Available in 9 gauge finish 10 gauge core fused & bonded vinyl coated wire per ASTM F668, class 2B	✓
Single wall slats with staples	✓
Slats meet ASTM F3000 and F3000M designations	✓
Available in a 25' roll 5' minimum increments thereafter	✓
Seven year pro-rata limited warranty	✓

Standard Wire Colors



Standard Slat Colors



Colors are approximations. Exact representation of colors in printing is difficult. Please refer to actual color samples for accurate matching. **Samples available upon request.**

BudgetLink® comes in two degrees of privacy - Privacy for near total privacy or Semi-Privacy for a more open look. One will surely provide the appearance and security you need.

HDPE Technical Properties

Property	Values
Melt Index	(.6) A low melt index indicates improved stress and crack resistance.
Density	(.957) Polyethylene ranges anywhere from .914 to .960 in density. A higher density yields maximum stiffness without becoming overly brittle.
Minimum Temp.	(-76° F) Polyethylene stays flexible even at this temperature extreme.
Maximum Temp.	(250° F) Polyethylene does not distort until reaching this temperature.
Tensile Strength	(3,700 psi) Material will not suffer distortion at lesser loads or impacts.



Privacy
Approximately 98%



Semi-Privacy
Approximately 75%



YOUR TOTAL FENCING SOURCE

COMMERCIAL, INDUSTRIAL & RESIDENTIAL FENCE PRODUCTS AND ACCESSORIES FOR THE FENCE PROFESSIONAL!