

# NOODLE LINK™ PLUS (2" mesh - near-total privacy)



**NOODLE LINK™ PLUS** provides the greatest amount of privacy of all the **NOODLE LINK™** products.

It features double-wall slats with specially designed wings on each side of the slat that wedge the slats tightly into the 2 inch mesh. The slats are secured in place at both **the top and bottom** of the fence by flexible round tubes. And, since your fence comes with the noodles and slats pre-inserted at our manufacturing facility you do not need to stuff them into the chain link.

**NOODLE LINK™ PLUS** is easy to install, costs less than most other chain link fence systems and it creates a beautifully finished fence your customers will love and appreciate.



**2 inch Chain Link Fence with the SLATS and NOODLE locked and Already in the Wire!**

**Most cost-effective privacy chain link fence!**



**NOODLE LINK PLUS™** provides approximately 98% or near-total privacy and is available in several wire weights and finishes, slat colors and heights. It meets ASTM designations, and we guarantee it, too.



**"Where Innovation Meets Expectation"**



## Technical Data

### NOODLE LINK™ PLUS Specifications

Double wall slats	✓
Wind load and privacy factor - approximately (Based on wire/mesh used-stretch tension)	98%
2" x 2" Mesh	✓
Manufactured up to 12' high	✓
Available in 9 gauge galvanized before weaving (GBW) per ASTM A392 and A817, Type II, class IV wire (1.20 oz.)	✓
Available in 11 gauge galvanized before weaving (GBW) per ASTM A392 and A817, Type II, class IV wire (1.20 oz.)	✓
Available in 9 gauge galvanized before weaving (GBW) per ASTM A392 and A817, Type II, class V wire (2.0 oz.)	✓
Available in 9 gauge finish 10 gauge core fused & bonded vinyl coated wire per ASTM F668, class 2B - 7 colors available	✓
Available in 8 gauge finish 9 gauge core fused & bonded vinyl coated wire per ASTM F668, class 2B - 7 colors available	✓
Available in 9 gauge aluminized before weaving wire per ASTM A491, Type 1	✓
Slats meet ASTM F3000 and F3000M designations	✓
Available in a 25' roll 5' minimum increments thereafter	✓
Fifteen year pro-rata limited warranty	✓

### Installation Instructions

Assemble the frame work, top rail, loop caps, etc.



Insert the needle and connect the rolls same as regular chain link fence. Stand the fence up to the posts and top rail, loosely attach to the top rail, attach tension bar and stretch wire into place. **Do not cut the noodle until you have stretched the wire.**



Install three (3) slats in space between sections.




Cut the excess noodle halfway between the two selvages, so both ends touch and using the hog ring pliers hog ring both ends of the noodle to the wire.

**Caution: If you trim the Noodle before stretching the wire, you may end up with not enough Noodle.**

**HDPE Technical Properties Available on request.**

### Standard Wire Colors



### Standard Slat Colors



Colors are approximations. Exact representation of colors is difficult. Please refer to actual color samples for accurate matching. **Samples available upon request.**



## YOUR TOTAL FENCING SOURCE

COMMERCIAL, INDUSTRIAL & RESIDENTIAL FENCE PRODUCTS  
AND ACCESSORIES FOR THE FENCE PROFESSIONAL!