

PrivacyMaster® (2" mesh — near total privacy)



PrivacyMaster® fence is distinguished by smaller mesh and the unique look of Winged Slats “pre-woven” into the mesh. Specially designed “wings” on Winged Slats provide a tight, snug fit in the chain link and offer approximately a 90 percent wind load and privacy factor (based on wire/mesh used-stretch tension). This fence provides the finishing touch to any property.

Benefits:

- Superior privacy
- Cost-efficient solution for most settings
- Less installation time saves labor costs
- Low Maintenance
- Effective wind screen
- Enhances the appearance of the property
- Acts as exceptional sound barrier
- Virtually theft resistant
- Virtually unclimbable

Heavy-duty HDPE Slats

PrivacyLink® features strong and durable double wall slats “pre-woven” into the wire mesh. Choose from a wide variety of colors and styles. There’s something just right for whatever your needs might be.

Galvanized Chain Link Fencing

We fabricate our chain link mesh using only the highest grade 9 or 11 gauge galvanized wire. Our state-of-the-art manufacturing process ensures a consistent weave and product quality.

Vinyl Coated Chain Link Fencing

We also offer a fused and bonded vinyl coated chain link mesh that is color coordinated to seven of our standard slat colors. And, we guarantee it for years of trouble-free use.

ASTM Designations

Meets ASTM Designations (see chart on the next page)



Technical Data

PrivacyMaster® Specifications	
Wind load and privacy factor - approximately (Based on wire/mesh used-stretch tension)	90%
2" x 2" Mesh	✓
Manufactured up to 12' high	✓
Available in 9 gauge galvanized before weaving (GBW) per ASTM A392 and A817, Type II, class IV wire (1.20 oz.)	✓
Available in 11 gauge galvanized before weaving (GBW) per ASTM A392 and A817, Type II, class IV wire (1.20 oz.)	✓
Available in 9 gauge galvanized before weaving (GBW) per ASTM A392 and A817, Type II, class V wire (2.0 oz.)	✓
Available in 9 gauge finish 10 gauge core fused & bonded vinyl coated wire per ASTM F668, class 2B - 7 colors available	✓
Available in 8 gauge finish 9 gauge core fused & bonded vinyl coated wire per ASTM F668, class 2B - 7 colors available	✓
Available in 9 gauge aluminized before weaving wire per ASTM A491, Type 1	✓
Self locking double wall slats without staples	✓
Slats meet ASTM F3000 and F3000M designations	✓
Available in a 25' roll 5' minimum increments thereafter	✓
Fifteen year pro-rata limited warranty	✓

Standard Wire Colors



Standard Slat Colors



Colors are approximations. Exact representation of colors is difficult. Please refer to actual color samples for accurate matching. **Samples available upon request.**

PrivacyMaster®'s double wall slats fit snugly into the galvanized steel or vinyl coated chain link mesh to provide 90% or near total privacy. They make an exceptional boundary for business complexes and residential property as well as providing outstanding security and beauty.

HDPE Technical Properties

Property	Values
Melt Index	(.6) A low melt index indicates improved stress and crack resistance.
Density	(.957) Polyethylene ranges anywhere from .914 to .960 in density. A higher density yields maximum stiffness without becoming overly brittle.
Minimum Temp.	(-76° F) Polyethylene stays flexible even at this temperature extreme.
Maximum Temp.	(250° F) Polyethylene does not distort until reaching this temperature.
Tensile Strength	(3,700 psi) Material will not suffer distortion at lesser loads or impacts.



YOUR TOTAL FENCING SOURCE

COMMERCIAL, INDUSTRIAL & RESIDENTIAL FENCE PRODUCTS AND ACCESSORIES FOR THE FENCE PROFESSIONAL!