



# Poly( Vinyl Chloride) (PVC)- Coated Steel Chain Link Fence Fabric

Class 1 - Extruded

ASTM F668, Federal Specification RR-F-191 Type IV, AASHTO M-181 Type IV

## PRODUCT NAME

SPSV Extruded Poly (Vinyl Chloride)- PVC Coated Steel Chain Link Fence Fabric

## MANUFACTURER

**Stephens Pipe and Steel, LLC**  
**Manufacturing Locations:**

Stephens Pipe and Steel, LLC  
1413 Steve Warriner Drive  
Russell Springs, Kentucky 42642

Stephens Pipe and Steel, LLC  
4301 46<sup>th</sup> Street  
Bladensburg, Maryland 20710

Stephens Pipe and Steel  
2891 State Hwy 160  
Warrior, Alabama 35180

## PRODUCT DESCRIPTION

### Basic Use:

Extruded fabric is a vinyl coated, high strength galvanized steel, chain link fence fabric for industrial, commercial and institutional application. Extruded fabric is the highest quality available and is used in numerous federal, state, civil, and military specifications.

### Composition and Materials:

The galvanized steel core wire for producing fused PVC coated steel chain link fence fabric is produced by cold-drawing good commercial grade steel rod into wire of the appropriate diameter. The steel rod from which the wire is drawn is produced by the open hearth, electric furnace or basic oxygen process. The galvanized coating is produced by passing the cleaned wire through a bath of molten zinc which conforms to ASTM B6.

The extruded PVC coating is produced by extruding PVC polymer over the galvanized core wire. A coating of PVC up to 0.025 in. (0.64 mm) is achieved in the extruding process.

### Standards:

ASTM B 6 Slab Zinc  
ASTM F567 Installation of Chain Link Fence  
ASTM F668 Poly(Vinyl Chloride) (PVC ) and Other Organic Polymer-Coated Steel Chain Link Fence Fabric, Class 1  
Federal Specification RR-F-191 K1 D Fencing, Wire and Post Metal  
(Chain-Link Fence Fabric), Type IV

## TECHNICAL DATA

### General:

The manufacturer, if requested, will supply samples and certification that all materials furnished fully comply with the appropriate specifications.

### Chain Link Fence Fabric:

The base metal of the chain link fence fabric is composed of commercial quality, medium-carbon galvanized (zinc coated) steel wire. The vinyl coating is extruded to galvanized steel wire. This process ensures a coating free of voids, as well as a smooth surface appearance. Vinyl coating thickness, galvanized coating weight, and wire tensile strength conform to Federal Specification RR-F-191, ASTM F668, Class 1. The wire is PVC coated before weaving and is free and flexible at all joints. Unless otherwise specified, fabric woven in 2 in. (50 mm) mesh, under 72" (1,830 mm) in height, is knuckled at both selvages; fabric 72" (1,830mm) high and over is knuckled at one selvage and twisted at the other. All fabrics woven into meshes under 2 in. (50 mm) have both selvages knuckled.

### Wire Diameter

Core wire sizes shall be one of the following diameters.

.192, .148, .120, .105, or .080

### Wire Coating:

Only plasticized poly(vinyl chloride) (PVC) with a low temperature (-20 °C; -4°F) plasticizer and no extenders or extraneous matter other than the necessary stabilizers and pigments, is used. The PVC coating resists attack from

prolonged exposure to dilute solutions of most common mineral acids, seawater, and dilute solutions of most salts and alkali

### ASTM Color System:

Standard colors conform to ASTM F934 and include:

Enso	Bro wn	B lack
Green	27.76	22.30
28.61	3.37	-0.09
-12.59	4.28	-0.85
1.95		

Other colors are available by special order.

Coating Adhesion: The PVC coated wire shall pass the test for adhesion contained in ASTM F668 for Class 1 chain link fabric.

## INSTALLATION

Install fence in accordance with ASTM Practice 567. Handle all PVC coated material with care. If PVC coating is damaged during installation, contractor must replace or repair the material at own expense.

## AVAILABILITY AND COST

Availability: PVC-coated steel chain link fence fabric is available for shipment throughout the United States and worldwide.

Cost: Material costs may vary depending on specific requirements. Costs may be obtained through all Stephens Pipe Service Centers.

## WARRANTY

Extruded PVC coated steel chain link fence fabric is warranted for 15 years against failure due to rust or corrosion.

## MAINTENANCE

Periodic inspection is recommended but no routine maintenance is required.



800.451.2612

ADVANTAGE  
ONE  
SOURCE