



Poly(Vinyl Chloride) (PVC)- Coated Steel Chain Link Fence Fabric

Class 2a - Extruded and Bonded
ASTM F668, Federal Specification RR-F-191 Type IV, AASHTO M-181 Type IV

PRODUCT NAME

SPSV Extruded and Bonded Poly (Vinyl Chloride)- PVC Coated Steel Chain Link Fence Fabric

MANUFACTURER

Stephens Pipe and Steel, LLC Manufacturing Locations:

Stephens Pipe and Steel, LLC
2224 E. Hwy. 619
Russell Springs, Kentucky 42642

Stephens Pipe and Steel, LLC
4301 46th Street
Bladensburg, Maryland 20710

Stephens Pipe and Steel
2891 State Hwy 160
Warrior, Alabama 35180

PRODUCT DESCRIPTION

Basic Use:

Extruded and bonded fabric is a vinyl coated, high strength galvanized steel, chain link fence fabric for industrial, commercial and institutional application. Extruded and bonded fabric is the highest quality available and is used in numerous federal, state, civil, and military specifications.

Composition and Materials:

The galvanized steel core wire for producing fused and adhered PVC coated steel chain link fence fabric is produced by cold-drawing good commercial grade steel rod into wire of the appropriate diameter. The steel rod from which the wire is drawn is produced by the open hearth, electric furnace or basic oxygen process. The galvanized coating is produced by passing the cleaned wire through a bath of molten zinc which conforms to ASTM B6.

The extruded and bonded PVC coating is produced by first applying a primer/adhesive bonding agent to the galvanized core wire to which the PVC is bonded. A minimum coating of 0.015 (0.38mm) PVC up to 0.025 in. (0.64mm) is then extruded and bonded to the wire.

Standards:

ASTM B 6 Slab Zinc
ASTM F567 Installation of Chain Link Fence
ASTM F668 Poly(Vinyl Chloride) (PVC) and Other Organic Polymer-Coated Steel Chain Link Fence Fabric, Class 2a
Federal Specification RR-F-191 K/1 D Fencing, Wire and Post Metal (Chain-Link Fence Fabric), Type IV
American Association of State Highway Transportation Officials (AASHTO) M-181 Chain Link Fence, Type IV, Class A

TECHNICAL DATA

General:

The manufacturer, if requested, will supply samples and certification that all materials furnished fully comply with the appropriate specifications.

Chain Link Fence Fabric:

The base metal of the chain link fence fabric is composed of commercial quality, medium-carbon galvanized (zinc coated) steel wire with a minimum 80,000lb tensile strength and 1290lb breaking load. The vinyl coating is bonded to a chemical bonding layer applied to galvanized steel wire. This process ensures a tightly bonded coating free of voids, as well as a smooth surface appearance. Vinyl coating thickness, galvanized coating weight, and wire tensile strength conform to Federal Specification RR-F-191, ASTM F668, Class 2a, and AASHTO M-181 Type IV, Class A, as shown in Table 1. The wire is PVC coated before weaving and is free and flexible at all joints. Unless otherwise specified, fabric woven in 2 in. (50 mm) mesh, under 72" (1,830 mm) in height, is knuckled at both selvages; fabric 72" (1,830mm) high and over is knuckled at one selvaige and twisted at the other. All fabrics woven into meshes under 2 in. (50 mm) have both selvages knuckled.

Wire Coating:

Only plasticized poly(vinyl chloride) (PVC) with a low temperature (-20 °C; -4°F) plasticizer and no extenders or extraneous matter other than the necessary stabilizers and pigments, is used. The PVC coating resists attack from prolonged exposure to dilute solutions of most common mineral acids, seawater, and dilute solutions of most salts and alkali.

ASTM Color System:

Standard colors conform to ASTM F934 and include:

Color	Green	Brown	Black
Enso	28.61	27.76	22.30
	-12.59	3.37	-0.09
	1.95	4.28	-0.85

Other colors are available by special order.

Coating Adhesion: The PVC coated wire shall pass the test for adhesion contained in ASTM F668 for Class 2a chain link fabric.

INSTALLATION

Install fence in accordance with ASTM Practice 567. Handle all PVC coated material with care. If PVC coating is damaged during installation, contractor must replace or repair the material at own expense.

AVAILABILITY AND COST

Availability: PVC-coated steel chain link fence fabric is available for shipment throughout the United States and worldwide.

Cost: Material costs may vary depending on specific requirements. Costs may be obtained through all Stephens Pipe Service Centers.

WARRANTY

Extruded and adhered PVC coated steel chain link fence fabric is warranted for 15 years against failure due to rust or corrosion.

MAINTENANCE

Periodic inspection is recommended but no routine maintenance is required.

TECHNICAL SERVICES

Technical services are available. Call your sales representative for assistance.



800.451.2612

ADVANTAGE
ONE
SOURCE